

2.2. SPINDLE MOTOR BİLGİLERİ

Dimensions





A	1.05" (26.54mm)	C	5.20" (86.15mm)	E	8.07" (204.97mm)
B	1.62" (41.15mm)	D	6.03" (153.16mm)	F	3.10" (78.74mm)

430XHD Series

ER11 - 1/4"		ER11 - 6mm	
Speed RPM	Part #	Speed RPM	Part #
25,000	34422	25,000	34423
30,000	34432	30,000	34433
40,000	34442	40,000	34443

Accessories

Model	Part #
High Flow Filter / Regulator / Extractor	30008
Coolant Guard	11060
Carrying Case	11300

General Specifications	*430XHD*
Speed RPM	25,000 / 30,000 / 40,000
Power Rating hp (kW)	1.2 (.90) / 1.3 (.98) / 1.4 (1.04)
Inlet Air Pressure	90 PSI (6,2 Bar)
Air Consumption Idle cfm (l/s)	16 (7.55) / 17 (8.02) / 18 (8.50)
Air Consumption Working Flow cfm (l/s)	19 (8.97) - 40 (18.89)
Sound Level	Less Than 67 dBA
Max Shank Capacity	ER 11 - 1/4" (6mm)
Motor Weight	42 oz (1.19 kg)

Standard Equipment

Motor, 1/4" or 6mm collet, collet wrenches, rear exhaust, and 3/8" NPT air supply fitting.

Oil free 90PSI / 6.2BAR, clean, dry air supply required

Ceramic and angular contact bearing options available.